



i3TOUCH EX Experience

interactive excellence.

High end design

The i3TOUCH EX has a refined and sleek design with an ultra-slim bezel and aluminium accents that create a premium look and feel.



Natural writing

Enjoy a perfect touch and viewing experience. Thanks to the zero air gap technology we were able to achieve a pen-to-paper feeling.

Jot down ideas, share with everyone

Create, capture and share your ideas or notes in the integrated whiteboard solution. Share your notes instantly via email, USB or QR code.





Digital signage

Share announcements, upcoming events, emergency messages and school- or companywide information with the digital signage feature on our i3TOUCH EX display.



Magnetic pen holder

Two integrated magnetic pen holders for a more intuitive, more ergonomic, easy reach.

Present wirelessly from any device

No more need for additional hardware. Present your screen wirelessly from any device on the i3TOUCH. All you need is the free app.

•••

Multi-function button

A shortcut for different actions: freeze image to hide confidential information, take a screenshot, switch to your preferred video input source, or choose other actions.



8 Years warranty

We are proud of our quality products and so we offer a warranty of up to 8 years, which is exceptional in the market.

One cable connection

The i3TOUCH EX is a future-proof solution that allows the latest devices with a USB-C connection to be connected to the screen with one cable for image, power, touch and audio.



High precision IR

The i3TOUCH EX includes an improved IR technology with a more precise and accurate touch, up to 30% more accurate than regular IR, and improved object recognition.



The combination of a motion and light sensor will optimize your viewing experience to all lighting conditions and keep energy consumption balanced.



Intuitive interface

Easily access your apps, change and rename input sources on the home screen, and navigate via the side menu.

PRODUCT INFORMATION	65″	75″	86″		
Model name	i3TOUCH EX65	i3TOUCH EX75	i3TOUCH EX86		
Product series	i3TOUCH Excellence - Interactive Flat Pan	el Displays			
DISPLAY SPECIFICATIONS					
Display technology	Liquid Crystal Display (LCD) with DirectLI	ED lighting			
Panel Type	IPS-ADS	IPS-ADS	IPS		
Panel active screen area	1431 x 806 mm (56.32" x 31.71")	1650 x 928 mm (64.96" x 36.53")	1895 x 1066 mm (74.61" x 41.97")		
Display aspect ratio	16:9				
Display native resolution	3840 x 2160 pixels - 4K Ultra High Definitio	on			
Brightness (typical)	400 cd/m²				
Contrast ratio (typical)	1200:1				
Dynamic contrast ratio	4000:1				
Viewing angle	178° / 178°				
Colour depth	1.073 billion colors (10 bit)				
Response time (typ.)	8 ms	8 ms	8 ms		
Refresh rate	60 Hz (@ UHD)				
Pixel pitch	0.372 x 0.372 mm	0.4297 x 0.4297 mm	0.4935 x 0.4935 mm		
Supported orientation	Landscape				
Glass	4 mm Hardened Anti-Reflection Safety Glo	ass (MOHS 7)			
Life time	50,000 hours				
Integrated loudspeakers	2 x 16 Watt				
Air gap	zero air gap				
CONNECTIVITY					
Digital audio-video inputs					
Digital audio-video output					
	1x VGA (DE-15 male) +				
Analogue audio-video input	audio jack (3.5 mm TRS connector)				
Analogue audio output	Ix audio jack (3.5 mm TRS connector)				
Digital audio output					
USB data ports	1x USB 3.1 Type C (Incl. DisplayPort and Power Delivery up to 45 Watts)				
	1x USB 2.0, 3x USB 3.0				
	OPS-PC slot (JAE TX24 connector) 4K @ 6	50Hz			
Control input	1x COM DE-9 (RS-232 standard)				
	LAN: RJ-45 connector (100 Mbit/sec)				
Network	Wi-Fi: 2.4 / 5 GHz (802.11 a/b/g/n/ac)				
	Bluetooth: 4.2				
OPERATIONAL FEATURES					
Operating System	Android [™] 8.0				
A	RAM: 3 GB				
Architecture	ROM: 32 GB				
	CPU: ARM A73+A53				
	GPU: Mali G51				
		ition			
	GPU: Mali G51	ition			
	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn	ition			
Interactive touch	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs	ition			
Interactive touch	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs Touch Connection: 2x USB-B				
Interactive touch	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs Touch Connection: 2x USB-B Recognition: Finger or passive stylus				
Interactive touch Supported Compatibility	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs Touch Connection: 2x USB-B Recognition: Finger or passive stylus Response time: < 4 ms (single touch), < 10 m	ms (max touch inputs)			
	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs Touch Connection: 2x USB-B Recognition: Finger or passive stylus Response time: < 4 ms (single touch), < 10 m Accuracy: ± 1 mm	ms (max touch inputs)			
Supported Compatibility	GPU: Mali G51 Technology: V-Sense Infrared Touch recogn Input Detection: 20 touch inputs Touch Connection: 2x USB-B Recognition: Finger or passive stylus Response time: < 4 ms (single touch), < 10 m Accuracy: ± 1 mm Windows, Android, Macintosh OS X, Linux, 18 hours / day	ms (max touch inputs) Chrome OS Ilish, Czech, Swedish, Finnish, Norwegian	, Spanish, Italian, Portuguese, Greek, Romani inese, Korean, Hungarian		

Product dimensions	1489 × 897 × 86mm	1710×1020×86mm	1957.2×1160×86mm		
Net product weight	39,65kg	53,70kg	68,85kg		
Packaging size	1656×204×1050mm	1860×280×1170mm	2211×280×1370mm		
Packaged weight	53,70kg	72,00kg	96,45kg		
Mounting pattern	600×400mm	800×400mm	800×600mm		
Color	Black front bezel, black back cabinet				
VARRANTY					
Standard warranty	5 years				
Extended warranty	for education entities: 8 years (via registration)				
(optional)	for corporate entities: 8 years (available for purchase)				
CCESSORIES					
Included	User Manual, Remote Control, Power Supply Cord, HDMI Cable (3 meter), USB cable (5 meter), 2x passive stylus, Wall Mount, WiFi Module, USB-C Cable (1.5 meter)				
Optional	i3FLOORSTAND series – Display stands and floorlifts				
	i3COMPUTER OPS				
	i3ALLSYNC HDMI Transmitter, i3ALLSYNC HDMI Storage				
EGULATORY INFORMATIO	Ν				
Product type approval	CE, FCC				
OFTWARE FEATURES	,				
i3NOTES Whiteboarding	Make annotations and share immediately with every device.				
i3OVERLAY Screen annotation	Write on top of every image/app/site & sav	ve your content in i3NOTES+			
ELECTRICAL PROPERTIES					
Power voltage	100 ~ 240 Volt - 50/60 Hz				
i ower vonage					
Power consumption		150 Watt	168 Watt		
Operating temperature	0° C to 40° C				
Operating humidity	10% to 90% RH non-condensing				
C	-20° C to 40° C				
Storage temperature	10% to 90% RH non-condensing				
	10% to 90% RH non-condensing				
	10% to 90% RH non-condensing 5,000 meters				
Storage humidity Maximum operational altitude	5,000 meters				
Storage humidity Maximum operational altitude	5,000 meters	Client laptop and mobile device r	equirements		
Storage humidity Maximum operational altitude	5,000 meters		-		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS	5,000 meters Laptops & Tablet PCs Windows 10 or newer	iPads, iPhones & iPods	Android Tablets & Phones Android 6.0		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System	5,000 meters 5,000 meters 6 Laptops & Tablet PCs Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS	5,000 meters ; Laptops & Tablet PCs Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB	iPads, iPhones & iPods iOS version 8.0 or newer	Android Tablets & Phones Android 6.0 or newer		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System Minimum Required	5,000 meters 5,000 meters 6 Laptops & Tablet PCs Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System Minimum Required	5,000 meters 5,000 meters Windows 10 or newer OSX 10.10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to AMD's CPU When i3ALLSYNC is deployed into connection with a minimum bandw	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5 or newer o the existing network , the host and th idth of 20 Mbps. When running HD co n, the overall performance is dependen	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System Minimum Required NETWORK REQUIREMENTS Network and Internet Access	5,000 meters 5,000 meters Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to AMD's CPU When i3ALLSYNC is deployed into connection with a minimum bandw Mbps. Like any network application	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5 or newer o the existing network , the host and th idth of 20 Mbps. When running HD co n, the overall performance is dependen	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with Android 6.0 or newer he clients require wired or wireless network ontent, increase the minimum bandwidth to 50		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System Minimum Required NETWORK REQUIREMENTS Network and Internet Access FUNCTIONALITY	5,000 meters 5,000 meters Windows 10 or newer OSX 10.10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to AMD's CPU When i3ALLSYNC is deployed into connection with a minimum bandw Mbps. Like any network application required to update the i3ALLSYN	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5 or newer o the existing network , the host and th idth of 20 Mbps. When running HD co n, the overall performance is dependen IC receiver app.	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with Android 6.0 or newer he clients require wired or wireless network ontent, increase the minimum bandwidth to 50 nt on available bandwidth. Internet access is al		
Storage humidity Maximum operational altitude SALLSYNC REQUIREMENTS Operating System Minimum Required NETWORK REQUIREMENTS Network and Internet Access FUNCTIONALITY Screen mirroring from any dev	5,000 meters 5,000 meters Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to AMD's CPU When i3ALLSYNC is deployed into connection with a minimum bandw Mbps. Like any network application	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5 or newer o the existing network , the host and th idth of 20 Mbps. When running HD co n, the overall performance is dependen	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with Android 6.0 or newer he clients require wired or wireless network ontent, increase the minimum bandwidth to 50 nt on available bandwidth. Internet access is al mirroring.		
Storage humidity Maximum operational altitude 3ALLSYNC REQUIREMENTS Operating System Minimum Required NETWORK REQUIREMENTS Network and Internet Access FUNCTIONALITY	5,000 meters 5,000 meters Windows 10 or newer OSX 10.10 or newe Intel Core 2Duo , 2.3Ghz, 2GB RAM, Equivalent specification to AMD's CPU When i3ALLSYNC is deployed into connection with a minimum bandw Mbps. Like any network application required to update the i3ALLSYN	iPads, iPhones & iPods iOS version 8.0 or newer iPad 3 / iPhone 5 or newer o the existing network , the host and th idth of 20 Mbps. When running HD ca n, the overall performance is dependen IC receiver app. - Support up to 6 split-screens - Support AirPlay and Googe	Android Tablets & Phones Android 6.0 or newer Phones/Tablets with Android 6.0 or newer he clients require wired or wireless network ontent, increase the minimum bandwidth to 50 nt on available bandwidth. Internet access is al mirroring.		

Sales contact: sales@i3-technologies.com Support contact: www.i3-technologies.com/en/warranty-support



52mm [2.05]

900 mm [35.44] 833 mm [32.81] 806 mm [31.71]



Ę


۳Ű

75″

1711 mm 86mm 54mm 24mm 1674 mm (OPENING) 456mm 1650 mm(ACTIVE AREA) 800mm . . . 928 mm (ACTIVE AREA) 957 mm (OPENING) 00mm i"_INC 1028 mm j 87 mm

ς.








1490 mm [58.68] 1453 mm [57.21] 1431 mm [56.32]

DIC

86mm [3.39]








· / ······

V.





i 7

